

## Mullard "Tropical Fish" Capacitors

Order Code	Capacitance	Rated Voltage	Tolerance	Body size: length * width * height (mm)	Leadout size: diameter * length (mm)	Pitch (mm)	price exc. VAT
TROP-010	0.001uF	250Vdc	10%	12 * 4 * 8	0.6 * 22	11	£ 0.71
TROP-020	0.001uF	250Vdc	20%	11 * 4 * 7	0.6 * 22	10	£ 0.63
TROP-030	0.0012uF	250Vdc	10%	12 * 4 * 9	0.6 * 22	10	£ 0.71
TROP-040	0.0022uF	250Vdc	10%	12 * 4 * 9	0.6 * 20	10	£ 0.71
TROP-050	0.0027uF	250Vdc	10%	12 * 4 * 9	0.6 * 20	10	£ 0.71
TROP-060	0.0033uF	250Vdc	10%	12 * 4 * 8	0.6 * 20	10	£ 0.71
TROP-070	0.0039uF	250Vdc	10%	11 * 4 * 7	0.6 * 22	10	£ 0.71
TROP-080	0.0047uF	250Vdc	10%	12 * 4 * 8	0.6 * 20	10	£ 0.71
TROP-090	0.0056uF	250Vdc	10%	12 * 4 * 8	0.6 * 20	10	£ 0.71
TROP-100	0.0068uF	250Vdc	10%	12 * 5 * 8	0.6 * 20	10	£ 0.71
TROP-110	0.0082uF	250Vdc	10%	11 * 4 * 7	0.6 * 20	10	£ 0.71
TROP-120	0.01uF	250Vdc	10%	12 * 4 * 8	0.6 * 22	10	£ 0.71
TROP-130	0.01uF	250Vdc	20%	11 * 4 * 7	0.6 * 22	10	£ 0.63
TROP-140	0.01uF	630Vdc	20%	11 * 4 * 7	0.6 * 22	10	£ 0.63
TROP-150	0.012uF	100Vdc	10%	12 * 4 * 7	0.6 * 22	10	£ 0.75
TROP-160	0.012uF	250Vdc	10%	11 * 4 * 7	0.6 * 22	10	£ 0.75
TROP-170	0.012uF	250Vdc	20%	12 * 4 * 7	0.6 * 22	10	£ 0.67
TROP-180	0.015uF	100Vdc	20%	12 * 4 * 8	0.6 * 22	10	£ 0.67
TROP-190	0.015uF	250Vdc	10%	12 * 4 * 8	0.6 * 22	10	£ 0.75
TROP-200	0.015uF	250Vdc	20%	12 * 4 * 8	0.6 * 22	10	£ 0.67
TROP-210	0.018uF	250Vdc	10%	11 * 4 * 7	0.6 * 22	10	£ 0.92
TROP-220	0.018uF	250Vdc	20%	11 * 4 * 7	0.6 * 22	10	£ 0.75
TROP-230	0.022uF	250Vdc	10%	12 * 4 * 8	0.6 * 22	10	£ 1.08
TROP-240	0.022uF	250Vdc	20%	12 * 4 * 8	0.6 * 22	10	£ 0.83
TROP-250	0.022uF	250Vdc	10%	12 * 4 * 7	0.6 * 22	10	£ 0.67
TROP-260	0.027uF	250Vdc	10%	12 * 4 * 8	0.6 * 8	10	£ 0.67
TROP-270	0.033uF	250Vdc	10%	12 * 4 * 7	0.6 * 20	10	£ 0.67
TROP-280	0.039uF	250Vdc	10%	12 * 4 * 7	0.6 * 22	10	£ 0.88
TROP-290	0.039uF	250Vdc	20%	12 * 4 * 7	0.6 * 8	10	£ 0.75
TROP-300	0.039uF	630Vdc	10%	16 * 6 * 10	0.7 * 24	14	£ 1.17
TROP-310	0.047uF	250Vdc	10%	12 * 4 * 8	0.6 * 22	10	£ 0.71
TROP-320	0.047uF	250Vdc	20%	12 * 4 * 8	0.6 * 22	10	£ 0.58
TROP-330	0.056uF	250Vdc	10%	11 * 4 * 8	0.6 * 22	10	£ 0.67
TROP-340	0.056uF	250Vdc	20%	11 * 4 * 8	0.6 * 8	10	£ 0.54
TROP-350	0.068uF	100Vdc	20%	11 * 4 * 8	0.6 * 8	10	£ 0.58
TROP-360	0.068uF	250Vdc	10%	11 * 4 * 8	0.6 * 22	10	£ 0.88
TROP-370	0.082uF	250Vdc	10%	11 * 4 * 9	0.6 * 20	10	£ 0.75
TROP-380	0.082uF	630Vdc	20%	20 * 6 * 11	0.8 * 28	20	£ 1.63
TROP-390	0.1uF	100Vdc	10%	11 * 4 * 8	0.6 * 8	10	£ 0.88
TROP-400	0.1uF	250Vdc	10%	12 * 5 * 8	0.6 * 20	10	£ 1.08

TROP-410	0.1uF	250Vdc	20%	12 * 5 * 8	0.6 * 20	10	£	0.83
TROP-420	0.15uF	100Vdc	10%	13 * 5 * 8	0.6 * 8	10	£	0.63
TROP-430	0.15uF	250Vdc	10%	15 * 5 * 8	0.8 * 25	15	£	0.88
TROP-440	0.15uF	250Vdc	20%	15 * 5 * 8	0.8 * 22	15	£	1.08
TROP-450	0.15uF	630Vdc	20%	21 * 8 * 14	0.8 * 25	18	£	1.33
TROP-460	0.18uF	100Vdc	10%	12 * 4 * 8	0.6 * 8	10	£	0.67
TROP-470	0.22uF	100Vdc	10%	15 * 5 * 9	0.8 * 8	15	£	0.67
TROP-480	0.27uF	100Vdc	20%	15 * 5 * 8	0.6 * 22	10	£	0.67
TROP-490	0.33uF	100Vdc	10%	17 * 6 * 9	0.8 * 10	14	£	0.67
TROP-500	0.33uF	250Vdc	20%	21 * 5 * 10	0.8 * 10	20	£	1.04
TROP-510	0.33uF	400Vdc	10%	20 * 8 * 13	0.8 * 30	20	£	1.50
TROP-520	0.33uF	250Vdc	10%	20 * 6 * 10	0.8 * 30	20	£	1.17
TROP-530	0.47uF	250Vdc	10%	21 * 6 * 11	0.8 * 26	20	£	1.17
TROP-540	0.56uF	100Vdc	10%	16 * 6 * 10	0.7 * 8	15	£	0.83
TROP-550	0.56uF	250Vdc	10%	20 * 7 * 12	0.8 * 30	20	£	1.25
TROP-560	0.56uF	400Vdc	10%	27 * 8 * 15	0.8 * 28	26	£	1.75
TROP-570	0.68uF	250Vdc	10%	20 * 7 * 12	0.8 * 25	19	£	1.42
TROP-580	0.68uF	400Vdc	10%	28 * 10 * 16	0.8 * 26	26	£	2.00
TROP-590	0.68uF	400Vdc	20%	28 * 10 * 16	0.8 * 26	26	£	1.75
TROP-600	0.82uF	400Vdc	10%	28 * 10 * 17	0.8 * 26	26	£	2.33
TROP-610	0.82uF	250Vdc	10%	27 * 7 * 12	0.8 * 26	26	£	1.33
TROP-620	1uF	250Vdc	10%	27 * 7 * 12	0.8 * 26	26	£	2.08
TROP-630	1uF	400Vdc	10%	28 * 10 * 19	0.8 * 25	25	£	2.33
TROP-640	2.2uF	250Vdc	10%	28 * 10 * 18	0.8 * 26	26	£	3.33