Audio Accessories MConnect

The mixture of silver plus 1% gold has proven itself excellently as capacitor film for the MCap® SUPREME SilverGold series. The resulting sound is so impressive that it was only natural to think of using this alloy for the internal wiring of electronic devices. Listening tests with individually isolated conductors quickly proved that SilverGold shows its superior strengths every bit as convincingly in this application as well.

Purity and elegance are the terms that automatically lend themselves to this exquisite material.

We offer the SilverGold wire in various diameters and insulated in PTFE.

For preparation we recommend MSolder soldering tin. (see p. 57)



Purity of silver: min. 99.97% typ. 99.99% Purity of gold: min. 99.97% typ. 99.99%

SGW110 SilverGold-wire 1,0 mm, non-insulated [€] SGW110WH SilverGold-wire 1,0 mm, PTFE-insulated, white * price/meter all prices on request SGW110YE SilverGold-wire 1,0 mm, PTFE-insulated, yellow * price/meter SGW210WH/YE SilverGold-wire 2 * 1,0 mm, PTFE-insulated, white/yellow * [€] price/meter SGW115 SilverGold-wire 1,5 mm, non-insulated [€] price/meter SGW115WH SilverGold-wire 1,5 mm, PTFE-insulated, white * [€] price/meter SGW115YE SilverGold-wire 1,5 mm, PTFE-insulated, yellow * [€] price/meter SGW215WH/YE

SilverGold-wire 2 * 1,5 mm, PTFE-insulated, white/yellow * price/meter * Insulation test voltage 2 500V DC, Max. operating voltage 250V AC Strength of PTFE insulation: min. 0.25 mm

SGW105

SilverGold-wire 0,5 mm, non-insulated

[€] price/meter

SGW105WH

SilverGold-wire 0,5 mm, PTFE-insulated, white *

[€] price/meter all prices on request

SGW105YE

SilverGold-wire 0,5 mm, PTFE-insulated, yellow * [€]

price/meter

SGW205WH/YE

SilverGold-wire 2 * 0,5 mm, PTFE-insulated, white/yellow * [€]

[€]

[€]

price/meter

SGW305WH

SilverGold-wire 3 * 0,5 mm, PTFE-insulated, white *

price/meter

SGW305YE

SilverGold-wire 3 * 0,5 mm, PTFE-insulated, yellow *

price/meter

[€]